

Kettle

Volume production for all your stocks, soups and sauces, ...

- 60, 100, 150 and 235 litres capacity.
- Cooking tank welded into 3mm main top.
- Double skin lid with Echtermann counterbalanced hinge.
- Insulated lid handle.
- Removable graduated strainer.
- Large bore rotary drain tap for ease of drainage.
- Integrated hot and cold water supply controlled from front fascia.

Direct heat

- Gas :** Heavy duty high performance stainless steel burners with integrated pilot light and thermocouple.
Thickness of the bottom of the tank : 3mm.
- Electric :** Heavy duty high performance electric elements controlled via energy regulator.
Thickness of the bottom of the tank : 8mm.

Indirect Heat

Triple skin tank, bottom of the tank : 3mm.
Manual filling of water. Control of overflow level.

- Gas :** Heavy duty high performance stainless steel burners with integrated pilot light and thermocouple.
Thickness of the bottom of the tank : 3mm.
- Electric :** Heavy duty high performance electric elements controlled via energy regulator. Security unit

Options

Offset drain pipe, 316L stainless steel tank for seafood, removable perforated lining, thermostatic regulation by digital control panel with or without offset.



Front fascia mounted control for hot and cold water supply.



Removable graduated strainer.



Direct heat models

Range	Front	Capacity	Power		Tank dim.
			Elec.	Gas	
800	800	100 L	-	18kW	Ø603x390
		150 L	12kW	19,5kW	Ø603x550
900	800	100 L	-	18kW	Ø603x390
		150 L	12kW	19,5kW	Ø603x550
1000	1000	235 L	-	22kW	640x620x600
	1000	150 L	12kW	19,5kW	Ø603x550
		235 L	-	22kW	640x620x600
	1200	345 L	-	34	900x725x530
	1500	500 L	-	45	1285x725x530

Indirect heat models

Range	Front	Capacity	Power		Tank dim.
			Elec.	Gas	
700	800	60 L	9kW	-	Ø500x360
800	800	60 L	9kW	-	Ø500x360
		100 L	13,5kW	18kW	Ø603x390
		150 L	18kW	19,5kW	Ø603x550
900	800	60 L	9 kW	-	Ø500x360
		100 L	13,5kW	18kW	Ø603x390
		150 L	18kW	19,5kW	Ø603x550
1000	1000	235 L	22,5kW	22kW	640x620x600
	1000	150 L	18kW	19,5kW	Ø603x550
		235 L	22,5kW	22kW	640x620x600