

Characteristics

External dimensions : 800 X 835 X 900
 Stainless steel top 18.10 planetary planetary brushed finish
 Top thickness : 3 mm
 body 1 mm in planetary brushed stainless steel
 Structure : 2 mm in stainless steel
 Stand with composite feet of 150 adjustable in height
 folded front edge radius 20 mm
 Back edge forming a chimney cover
 Front without any visible screw

Top


cast iron hot plate in 2 parts Dim : 800x600
 Plots to spread the heat
 Fireplace in brick refractory with
 protective shell of cast iron, central burner
 removable of 8kW
 cleaning tray under the plate
 Security by thermocouple with pilotlight
 secured and protected commands

Options :

s/s steel trim bardiam 38 - linear meter (X081001)
 gaz connection kit for hose per device (X901405)
 electric ignition gas burner (first gas burner) (X901501)

Base unit

Construction in stainless steel 18.10
 Structure 2 mm
 body 1 mm
 External dimensions : 800x724x650
 Interior dimensions : 600x656x380
 intermediate shelf
 Front without any visible screw
 Double skin doors
 Power 1,5 kW
 Regulation by thermostat 0-85°C



GAS



Gas power : 8kW

Gas connection : 15/21 MALE TAPERING

Gas appliances complying with standard NF EN 203.EN 437

Gas Directive 2009/142/EC

ELECTRIC



Electric power : 1.50kW

Elec Réserve : INTERNAL TERMINAL BOARD - Elec fitting
: 230V SINGLE

230V SINGLE(Si option électrique sélectionnée)

Electrical devices standard to the norm EN 60-335