



### Characteristics

External dimensions : 1200 X 835 X 900  
 Top in brushed 18.10 food grade stainless steel  
 Top thickness : 3 mm  
 body 1 mm in brushed stainless steel  
 Structure : 2 mm in stainless steel  
 Base feet made of composite of 150 adjustable in height  
 folded front edge radius 20 mm  
 Back edge forming a chimney cover  
 Front without any visible screw

### Top

6 open burners  
 removable burners with pilot light 6x6kw  
 Burner griddles in stainless steel, dimensions : 400x600  
 Stamped tank & cleaning tray  
 Security pilot and thermocouple  
 secured and protected commands

### Base unit

Construction in stainless steel 18.10  
 Structure 2 mm  
 body 1 mm  
 External dimensions : 1200x724x650  
 intermediate shelf  
 Front without any visible screw  
 Power 850 W  
 Regulation by thermostat 0-85°C  
 Dimension of the retort : 650x530x280  
 Walls insulated by mineral fibers  
 aluminium steam barrier  
 Power 10 kW thermostat 50 à 300°C  
 Removable steel bottom 6 mm thickness  
 Security pilot and thermocouple  
 stainless steel lateral walls  
 with levels holding griddles  
 Door to double wall insulated and balanced  
 Provided with one stainless steel griddle GN2/1

### Options :

s/s steel trim bardiam 38 - linear meter (X081001)  
 gaz connection kit for hose per device (X901405)  
 ignition 7 points (X901505)

**GAS**

Gas power : 46kW

Gas connection : 20/27 MALE TAPERING

Gas appliances complying with standard NF EN 203.EN 437

Gas Directive 90/396 / EEC

**ELECTRIC**

Electric power : 0.85kW

Elec Réservation : INTERNAL TERMINAL BOARD - Elec fitting  
: 230V SINGLE

230V SINGLE( Si option électrique sélectionnée)

Electrical devices standard to the norm EN 60-335