



Characteristics

External dimensions : 2000 X 836 X 270
 Single-piece top, stainless steel 18.10, planetary brushed finish
 Top thickness : 3 mm
 body 1 mm in brushed stainless steel
 Structure : 2 mm in stainless steel
 folded front edge radius 20 mm
 Back edge forming a chimney cover
 Front without any visible screw
 Single chimney, length 2000

Top

4 open burners
 removable burners with pilot light 4x4,8kw
 Stainless steel burner grill dimensions : 300x550
 Stamped tank & cleaning tray
 Solid top made of steel, dimensions : 400x550
 Plots to spread the heat
 Fireplace in brick refractory with
 Removable central burner (6KW)
 Security pilot and thermocouple
 secured and protected commands
 Special stainless steel plate 18.10 thickness 15 mm
 Dimensions : 340x515
 Power : 3 kW
 Heating by reinforced stainless steel resistance
 Leaned against the bottom of the plate
 1 heating zone controlled by independent thermostat
 Scraper included
 peripheral water trough for easy cleaning
 over-flow and draining stopper
 cleaning and waste water drawer
 Net 8L stainless steel tank thickness 20/10
 Power : 6 kW
 Efficiency: 12-25 kg/h 6x6 frozen french fries
 Thermostat 100-180°C positive security 220°C
 Heating by reinforced stainless steel resistances
 Draining by tap on the front
 1 stainless steel basket dimension : 240x190x140

Options :

s/s steel trim bardiam 38 - linear meter (X081001)
table for trim bar - 500mm (X081002)
table for trim bar - 800mm (X081003)
grille inox 300x275 pour feux 4,8kw (X901406)
electric ignition gas burnereach other gas burner (X901502)

GAS



Gas power : 25kW

Gas connection : 20/27 MALE TAPERING

Gas appliances complying with standard NF EN 203.EN 437

Gas Directive 90/396 / EEC

ELECTRIC



Electric power : 9.00kW

Elec Réservation : INTERNAL TERMINAL BOARD - Elec fitting
: 400V THREE + NEUTRAL

230V SINGLE(Si option électrique sélectionnée)

Electrical devices standard to the norm EN 60-335