



Characteristics

External dimensions : 400 X 836 X 900
 Top in brushed 18.10 food grade stainless steel
 Top thickness : 3 mm
 body 1 mm in brushed stainless steel
 Structure : 2 mm in stainless steel
 Base feet made of composite of 150 adjustable in height
 folded front edge radius 20 mm
 Back edge forming a chimney cover
 Front without any visible screw

Top

2 open burners
 removable burners with pilot light 2x7kw
 Brûleurs corps inox
 Burner griddles in stainless steel, dimensions : 400x600
 Stamped tank & cleaning tray
 Security pilot and thermocouple
 secured and protected commands

Base unit

Construction in stainless steel 18.10
 Structure 2 mm
 body 1 mm
 External dimensions : 400x724x650
 Interior dimensions : 330x656x310
 intermediate shelf
 Front without any visible screw
 Double skin door
 Power 850 W
 Regulation by thermostat 0-85°C

Options :

s/s steel trim bardiam 38 - linear meter (X081001)
 gaz connection kit for hose per device (X901405)
 electric ignition gas burner each other gas burner (X901502)
 ecoflam system for 2 burners 7kw (X901506)

GAS

Gas power : 14kW

Gas connection : 15/21 MALE TAPERING

Gas appliances complying with standard NF EN 203.EN 437

Gas Directive 90/396 / EEC

ELECTRIC

Electric power : 0.85kW

Elec Réservation : INTERNAL TERMINAL BOARD - Elec fitting
: 230V SINGLE

230V SINGLE(Si option électrique sélectionnée)

Electrical devices standard to the norm EN 60-335