



Characteristics

External dimensions : 1200 X 835 X 900
 Top in brushed 18.10 food grade stainless steel
 Top thickness : 3 mm
 body 1 mm in brushed stainless steel
 Structure : 2 mm in stainless steel
 Base feet made of composite of 150 adjustable in height
 folded front edge radius 20 mm
 Back edge forming a chimney cover
 Front without any visible screw

Base unit

Construction in stainless steel 18.10
 Structure 2 mm
 body 1 mm
 External dimensions : 1200x724x650
 Interior dimensions : 1000x656x380
 intermediate shelf
 Front without any visible screw
 Double skin doors
 Power 2,1 kW
 Regulation by thermostat 0-85°C

Options :

worktop cut out with removable salting tank (X080602)
 s/s steel trim bardiam 38 - linear meter (X081001)
 lateral swing door (X081111)
 neutral unit cut out for integration (X081112)
 electric outlet on front panel (X330311)
 stand for salamander on neutral unit (X901941)
 goose neck valve rotating (X902001)
 cold & hot water supply on water column 500mm (X902002)

ELECTRIC

Electric power : 2.10kW

Elec Réserve : - Elec fitting : 400V THREE

230V SINGLE(Si option électrique sélectionnée)
Electrical devices standard to the norm EN 60-335