



Characteristics

External dimensions : 500 X 1000 X 900
 Top in brushed 18.10 food grade stainless steel
 Top thickness : 3 mm
 body 1 mm in brushed stainless steel
 Structure : 2 mm in stainless steel
 Base feet made of composite of 150 adjustable in height
 folded front edge radius 20 mm
 Back edge forming a chimney cover
 Front without any visible screw

Base unit

Construction in stainless steel 18.10
 Structure 2 mm
 body 1 mm
 External dimensions : 500x724x650
 Interior dimensions : 430x656x430
 Front without any visible screw
 Double skin doors

Options :

worktop cut out with removable salting tank (X080602)
 s/s steel trim bardiam 38 - linear meter (X081001)
 table for trim bar - 500mm (X081002)
 lateral swing door (X081111)
 neutral unit cut outfor integration (X081112)
 sliding drawer for gn1/1 (X081113)
 connecting plate for foot removal (X087004)
 electric outlet on front panel (X330311)
 goose neck valverotating (X902001)
 cold&hot water supply on water column 500mm (X902002)

ELECTRIC



Electric power : 0.00kW

Elec Réserve : - Elec fitting :

230V SINGLE(Si option électrique sélectionnée)
Electrical devices standard to the norm EN 60-335