



### **Characteristics**

External dimensions : 1000 x 970 x 630  
Top in brushed 18.10 food grade stainless steel  
body 1 mm in brushed stainless steel  
Structure : 2 mm in stainless steel  
Base feet made of composite of 150 adjustable in height  
Front without any visible screw

### **Base unit**

Construction in stainless steel 18.10  
Structure 2 mm  
body 1 mm  
Dimension of the retort : 600x800x280  
Walls insulated by mineral fibers  
aluminium steam barrier  
Power 13,2 kW thermostat 50 à 300°C  
Removable steel bottom 6 mm thickness  
Security pilot and thermocouple  
stainless steel lateral walls  
with levels holding griddles  
Door to double wall insulated and balanced  
Provided with one stainless steel griddle

### **Options :**

gaz connection kit for hose per device (X901405)  
electric ignition gas burner (first gas burner) (X901501)

## GAS



Gas power : 13kW

Gas connection : 15/21 MALE TAPERING

Gas appliances complying with standard NF EN 203.EN 437

Gas Directive 90/396 / EEC

## ELECTRIC



Electric power : 0.00kW

Elec Réserve : - Elec fitting :

230V SINGLE( Si option électrique sélectionnée)

Electrical devices standard to the norm EN 60-335