

## CATERING RANGE KETTLE 150L GAS

### DIRECT HEAT - HW/CW SUPPLY



### Characteristics

External dimensions : 1000 X 1000 X 900  
 Top in brushed 18.10 food grade stainless steel  
 Top thickness : 3 mm  
 body 1 mm in brushed stainless steel  
 Structure : 2 mm in stainless steel  
 Base feet made of composite of 150 adjustable in height  
 folded front edge radius 20 mm  
 Back edge forming a chimney cover  
 Front without any visible screw

### Top

1 mm stainless steel double lid  
 equipment with echtermann hinge  
 Cuve in stainless steel 18.10 welded on the top  
 2mm thickness for the ferrule and 3mm for the bottom  
 Dimensions (ØxP) : 603x550  
 net capacity : 150 l.  
 Power: 19,5 kW  
 Lid handle with insulated end  
 HW/CW feeding by fixed tap  
 controlled on the front by 1/4 turn tap  
 with ceramic components  
 Drain Valve 40/49 with retractable handle  
 Removable strainer with level indication  
 Heating by gas ramps  
 Control by 3-positions gas valve  
 Security pilot and thermocouple  
 Lighting indicator  
 Electric ignition

### Options :

removable perforated lining for 235 l kettle (X294001)  
 offset drain pipe (X901802)  
 316l stainless steel kettle (X904001)

**GAS**

Gas power : 20kW

Gas connection : 15/21 MALE TAPERING

Gas appliances complying with standard NF EN 203.EN 437

Gas Directive 90/396 / EEC

**ELECTRIC**

Electric power : 0.10kW

Elec Réservation : INTERNAL TERMINAL BOARD - Elec fitting  
: 230V SINGLE

Electrical devices standard to the norm EN 60-335

**WATER/AIR**

Hot water fitting :15/21 FEMALE FLEX



Cold water fitting :15/21 FEMALE FLEX