










		Model	M2200	
		Code Production	LP613F	
Interface :				
				
	Overall Dimension (Width-Depth-Height) *open		mm	853x857(*1400)x1959 (*2274)
	Packaging Dimension (WxDxH)		mm	1000x950x2200
	Gross weight		Kg	191
	Net weight		Kg	181
	Volume		mc	2,10
	Rack size		mm	700 x 700
	Max door /hood opening		mm	850
	Max glasses/plate Height		mm	800
	General construction			double skin
	Door/hood Construction			double skin
	Tank construction			fully deep drawn
	Tank volume		liter	68
	Tank heating element		W	8.000
	Tank surface strainers			stainless steel
	Wash pump type			double flow
	Wash pump power		W	2.700
	Wash temperature		°C	55 (55—65)
	Boiler type			without pressure
	Boiler volume		liter	12
	Back-flow system			break tank
	Boiler heating element		W	8.000
	Rinse booster pump			YES
	Rinse booster pump power		W	200
	Rinse temperature		°C	80 (80-85)
	Rinse water consumption		Liter /rack	4
	Optimal external water pressure		bar	1 - 6
	Drain system			deep drain
	Drain filter			double filter
	Drain pump			standard built in
	Rinse aid dispenser			optional
	Detergent dispenser			optional
	Wash cycle		sec	120 - 240 - 360 - continuous
	Self cleaning cycle			YES
	Electric Power		W	10.700
	Electric Connection		V - ph - Hz	400V 3N 50Hz
	Fuse		A	20
	Steel generic basket		N°1	42305
	Electric cable			YES
	Drain hose			YES
	Fill hose			YES

